



### **Yellow Rubber Finger Protective Cover**

Electric Rubber Finger Protective Cover play a hand or human body protection, made of rubber, latex, plastic and other materials, with electricity proof, waterproof, acid and alkali resistance, chemical, oil proof function. Suitable for electric power industry, automotive and mechanical maintenance, chemical industry, precision installation.

**Yellow Rubber Finger Protective Cover** play a hand or human body protection, made of rubber, latex, plastic and other materials, with electricity proof, waterproof, acid and alkali resistance, chemical, oil proof function. Suitable for electric power industry, automotive and mechanical maintenance, chemical industry, precision installation.

#### **Product Parameter of the Yellow Rubber Finger Protective Cover:**

- ①Product name: **Yellow Rubber Finger Protective Cover**
- ②Material: EPDM NBR Silicon or Can Custom
- ③Logo: Can Custom
- ④Size: Can Custom
- ⑤Can Custom: Black or custom
- ⑥Application: Automotive
- ⑦Certifications: IATF16949 ,ISO14001:2015,ROHS,CMC, etc
- ⑧Delivery: 30 -50days after sample confirmation
- ⑨Sample: 25-30 days
- ⑩Payment: 30% deposit, 70% payment before shipment
- ⑪Package: PE bags, Cartons,Pallet
- ⑫Payment Terms: T/T,L/C and so on.
- ⑬Shipment Way: Vessel,Air,Express etc.

**Product Feature AND Application of the Yellow Rubber Finger Protective Cover:**

**Yellow Rubber Finger Protective Cover** is an important part of insulation protection in personal protective equipment. With the development of electric power industry and the popularization of live work technology, more stringent requirements are put forward for the safety of insulation gloves used in live work.

**Features:**

- ①resilience and fatigue resistance, because the rubber sleeve to expand and shrink operation, so the elasticity and fatigue resistance of rubber is particularly key, which lianxing rubber sleeve tensile strength reaches 10Mpa, elongation at break is > 600%. Permanent deformation is grade A.
- ②temperature resistance, because in some production links, the working environment is high temperature environment.
- ③oil resistance, because there are more oil in the field working environment, so oil resistance is also a parameter to consider.

④high friction coefficient, for loading and unloading links, friction is better for easy operation.

**Below is our industrial electric power silicone rubber parts:**

